



PROJECTORS
PA503X

Key Features

SuperColor: Amazing Color Accuracy | 3,600

Lumen Brightness | Energy Efficient SuperEco |

Reduced Input Latency



Product Description

The ViewSonic® PA503X price-performance projector features 3,600 lumens, native XGA 1024 x 768 resolution, and intuitive, user-friendly design. Exclusive SuperColor™ technology offers a wide color gamut for beautiful image production in nearly any environment. The PA503X also features extensive connectivity including HDMI, 2 x VGA, VGA out, Composite Video and audio in/out. An energy-saving SuperEco™ feature reduces power consumption and extends the lamp life by up to 15,000 hours*. With advanced audio-visual features, flexible connectivity options, and an affordable price, the PA503X is ideal for use in education and small business environments.

*Energy consumption and lamp life may vary based on actual usage and other factors.




1. Projection lens
2. IR remote sensor
3. Elevation foot
4. Focus / zoom rings

5. VGA x2
6. HDMI
7. Audio In/Out
8. AC In

9. Control Panel
10. Monitor Out
11. Kensington® Lock Slot
12. Video In


13. USB type Mini B
14. RS232



1024 x 768
RESOLUTION



3,600
LUMENS



1.96 ~ 2.15
THROW RATIO

Contact Sales

- call: 888.881.8781
- email: salesinfo@viewsonic.com
- visit: viewsonic.com

Display:

Type:	DLP
Resolution Type:	XGA
Resolution:	1024 x 768
Brightness (ANSI Lumens):	3,600
Throw Distance:	3.9 - 43 ft / 1.19 - 13.11 m
Throw Ratio:	1.96 ~ 2.15
Display Size (in.):	30 - 300 in. / 0.76 - 7.62 m
Keystone:	Vertical ($\pm 40^\circ$)
Lens:	1.1x optical zoom
Light Source (watt):	190
Light Source Life, Normal (hours):	4500
Light Source Life, Dynamic Eco-Mode (hours):	15000
Color Depth:	1.07B Color (R/G/B 10bit)
Dynamic Contrast Ratio:	22000:1
Aspect Ratio:	4:3

Video Signal:

Frequency Horizontal:	15K~102KHz
Frequency Vertical:	23~120Hz

Compatibility:

PC Resolution (max):	VGA (640 x 480) to WUXGA_RB (1920 x 1200)
Mac® Resolution (max):	VGA (640 x 480) to WUXGA_RB (1920 x 1200)

Connector:

Mini USB Type B(1), Audio Output (Mini Jack)(1), 3.5mm Audio In(1), Control (RS232)(1), HDMI 1.4(1), VGA In(2), VGA Out(1), Composite RCA Video In(1)

Audio:

Internal Speakers:	2W
--------------------	----

Power:

Voltage:	AC 100-240V (universal), 50-60Hz
Consumption (typical):	260W
Stand-by:	<0.5W

Operating Conditions:

Temperature:	32-104° F (0-40° C)
--------------	---------------------

Weight (imperial):

Net (lbs):	4.89
Gross (lbs):	7.14

Weight (metric):

Net (kg):	2.22
Gross (kg):	6.24

Dimensions (imperial) (WxHxD):

Packaging (in.):	14.37 x 11.81 x 7.4
Physical (in.):	11.57 x 8.58 x 4.33

Dimensions (metric) (WxHxD):

Packaging (mm):	365 x 300 x 188
Physical (mm):	294 x 218 x 110

General:

Regulations: FCC (including ICES-003), cTUVus

PACKAGE CONTENTS: PA503X projector, power cable, VGA cable, remote control, Quick Start Guide, ViewSonic Wizard CD (with User Guide)

Warranty: 3-year limited warranty on parts and labor, 1st year free Express Exchange® service**

Recycle/Disposal: Please dispose of in accordance with local, state or federal laws.

UPC: 766907905113

Accessories:

PGD-350, PJ-CASE-008, PJ-WMK-006, PM-FCP, RLC-108