

## Key Features

SuperColor: Amazing Color Accuracy | 3,600 Lumen  
Brightness | Energy Efficient SuperEco | Reduced Input  
Latency



## Product Description

The ViewSonic® PA503S price-performance projector features 3,600 lumens, native SVGA 800 x 600 resolution, and intuitive, user-friendly design. Exclusive SuperColor™ technology offers a wide color gamut for beautiful image production in nearly any environment. The PA503S also features extensive connectivity including HDMI, 2 x VGA, VGA out, Composite Video and audio in/out. An energy-saving SuperEco® feature reduces power consumption and extends the lamp life by up to 15,000 hours. With advanced audio-visual features, flexible connectivity options, and an affordable price, the PA503S is ideal for use in education and small business environments.



800 x 600  
RESOLUTION



3,600  
LUMENS



1.96 ~ 2.15  
THROW  
RATIO

### Contact Sales



call: 888.881.8781



email:  
salesinfo@viewsonic.com



visit: viewsonic.com

### Display:

Type:	DLP
Resolution Type:	SVGA
Resolution:	800 x 600
Brightness (ANSI Lumens):	3,600
Throw Distance:	3.9 ft - 43 ft (100" @ 13 ft)
Throw Ratio:	1.96 ~ 2.15
Display Size (in.):	30 - 300 in. / 0.76 - 7.62 m
Keystone:	Vertical (± 40°)
Lens:	1.1x Manual optical zoom / manual optical focus
Light Source (watt):	190
Light Source Life, Normal (hours):	4500
Light Source Life, Dynamic Eco-Mode (hours):	15000
Color Depth:	1.07B Color (R/G/B 10bit)
Dynamic Contrast Ratio:	22000:1
Aspect Ratio:	4:3

### Video Signal:

Frequency Horizontal:	15K~102KHz
Frequency Vertical:	23~120Hz

### Compatibility:

PC Resolution (max): VGA (640 x 480) to WUXGA\_RB (1920 x 1200)

Mac® Resolution (max): VGA (640 x 480) to WUXGA\_RB (1920 x 1200)

**Connector:**

Mini USB Type B(1), Audio Output (Mini Jack)(1), 3.5mm Audio In(1), Control (RS232)(1), HDMI 1.4(1), VGA Out(1), Composite RCA Video In(1), RGB Input(2)

**Audio:**

Internal Speakers: 2W

**Power:**

Voltage: AC 100-240V (universal), 50-60Hz

Consumption (typical): 260W

Stand-by: <0.5W

**Operating Conditions:**

Temperature: 32-104° F (0-40° C)

**Weight (imperial):**

Net (lbs): 4.89

Gross (lbs): 7.14

**Weight (metric):**

Net (kg): 2.22

Gross (kg): 3.24

**Dimensions (metric) (WxHxD):**

Packaging (mm): 365 x 300 x 188

Physical (mm): 294 x 218 x 110 Copyright © ViewSonic Corporation 2000-2017. All rights reserved. (06/29/2017 05:41 AM PST)

**Dimensions (imperial) (WxHxD):**

Packaging (in.): 14.37 x 11.81 x 7.4

Physical (in.): 11.57 x 8.58 x 4.33

**General:**

Regulations: FCC (including ICES-003), cTUVus

PACKAGE CONTENTS: PA503S projector, power cable, VGA cable, remote control, Quick Start Guide, ViewSonic Wizard CD (with User Guide)

Warranty: 3-year limited warranty on parts and labor, 1st year free Express Exchange® service\*\*

Recycle/Disposal: Please dispose of in accordance with local, state or federal laws.

UPC: 766907904710

**Accessories:**