

CP-X2515WN LCD PROJECTOR

PRELIMINARY

HITACHI
Inspire the Next

SPECIFICATIONS ARE SUBJECT TO CHANGE



Key Features

- Drawing Function w/Option TB-1 Tablet
- Intelligent Eco Mode w/ImageCare Technology
- Display via USB
- Input Source Naming
- Network Control, Maintenance and Security
- Wireless Presentation Ready

Projection Throw Chart

Screen Size 4:3		Throw Distance	
Diagonal	Width	Min	Max
30	24	32	39
60	48	68	82
80	64	92	111
100	80	116	140
150	120	175	211
200	160	235	283
300	240	354	426

Throw Ratio: 1.5 - 1.8 : 1 (distance : width)

Specifications

Display	Projection Technology	3LCD, 3 chip technology
	Resolution	XGA, 1024 x 768
	White Light Output	2,700 Lumens
	Color Light Output	2,700 Lumens
	Colors	16.7 million colors
	Aspect Ratio	4:3 / 16:9 / 16:10 compatible
	Contrast Ratio	3000 :1 w/active Iris
Lens & Operation	Throw Ratio (distance : width)	1.5 - 1.8 : 1
	Lens	Manual zoom x1.2
	Lamp Wattage	215W
	Expected Lamp Life	5,000 hours / 6,000* hours eco mode
	Expected Filter Life	5000* Hours
	Speaker Output	8W x 2
	Acoustic Noise Level	36 dB / 29 dB in Eco Mode
Compatibility	Keystone	+/- 30 degrees, vertical only
	Computer	VGA, SVGA, XGA, WXGA, WXGA+, SXGA+, UXGA (compressed), MAC 16"
	H-Sync	31.5 kHz - 106 kHz
	V-Sync	56 Hz - 120 Hz
	Composite Video	NTSC, NTSC 4.43, PAL, PAL-M, PAL-N, SECAM
	Component Video	480i, 480p, 576i, 720p, 1080i, 1080p
	HDMI	Video: 480i, 480p, 576i, 720p, 1080i, 1080p TMDS Clock 27 MHz - 150 MHz
Connectors	Digital Input	HDMI input x1
	Computer Input 1	15 pin D-sub x1
	Computer Input 2	15 pin D-sub x1
	Computer Monitor Output	15 pin D-sub x1
	Video Input	
	S-Video	Mini DIN 4 pin x1
	Composite Video	RCA jack x1
	Component Video	15 pin D-sub x2 (shared with analog computer 1/2)
	Audio Input	3.5mm stereo mini jack x2, RCA jack x1 (L/R)
	Audio Output	RCA jack x1 (L/R)
Ratings & Warranty	Network (LAN) Wired	RJ45 jack x1
	Network (LAN) Wireless	IEEE802.11b/g/n - Optional adaptor required
	USB	Type A x2(PC-less, wireless adapter, TB-1) Type B x1 (USB display or mouse control)
	Control Terminals	D-sub 9 pin plug x1 for RS232C
	Power Supply	AC 90 - 132V/AC 198 - 264V
	Power Consumption	310W
	Operating Temperature	40 - 95 F (5 - 35 C)
Dimensions (WxDxH)	12.5" x 11.3" x 3.9"	
Weight	8.15lbs	
Approvals	UL 60950-1 / cUL FCC Part 15 subpart B Class A	
Warranty	3 years	

1.800.HITACHI
hitachi-america.us/projectors

* Varies depending on the environment and conditions to be used.